Made in Germany!
Importer: Ltd "Abschliff Latvija"
Riga, A Čaka iela 107 K2
Phone: +371 67843844, 67843845
Fakss: +371 67272792
Mob.: +371 26177888
E-mail: info@abschliff.lv
www.abschliff.lv
https://www.facebook.com/Abschliff-Latvija-100679528475676/

Open: Monday to Friday – 9^{00}-18^{00}, Saturday- 10^{00}-14^{00}, Sunday – closed

Poseidon - varnish for surfaces with medium load

Descrption: One-component, quick-drying coating. It is designed for coating parquet and wood floors in apartments, with normal and medium wear. Giscode W2+, Blue Angel

Degree of gloss: semigloss, gloss

Application: Poseidon is rolled undiluted in 3 layers or rolled 1 x and cross-toweled 2 x and then rolled again 1 – 2 x.

Special instructions: unlike conventional, solvent-based finishes, Poseidon should be applied in rich layers. The material should not be excessively spread with the roller!

Primer alternatives: if for optical reasons (deep wood color) the use of a solvent-based primer is desired, UniQuick Primer is recommended. To reduce edge bonding in case of nervous wood species, e.g. beech, the Aqua-Seal FlexPrimer is recommended.

Draying: at 23°C/50% rel. humidity on a roll/stroke layer: after 3-4 hours grindable and carefully walkable. Spatula layer: approx. 10 - 20 min. With poor ventilation, lower temperature, other humidity and increased layer thickness, drying can be significantly delayed. Do not expose to wear, cover with carpets or apply care products for 8-14 days.

Consumption. Depending on the substrate and working method:
- 1 trowel layer approx. 30 ml/m^2 or approx. 33 m^2/l;
- 1 roll/stroke layer approx. 100 ml/m^2 or approx. 10 m^2/l.

Storage/transport: shelf life of original unopened packing is a min. 12 months for the finish provided that the material is transported and stored in a cool and dry place protected from freezing.

Factory sealed prefabricated parquet: Poseidon is not suitable for the re-sealing of factory coated prefabricated parquet and cork.

Packaging: 1l, 5l, 10l.

Cross reference: the following Technical Data Sheets should be observed:

1. General instructions of use for hardwood floor finishing products
2. Cleaning and maintenance of finished/oiled floors
3. Identification and safety instructions (MSDS)

Attention! Even when working with materials that contain a small amount of harmful substances, it is necessary to follow the generally accepted labor protection regulations. Keep the product out of the reach of children.