

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: XG20000AAJ10 AquaSeal ExoBloc
Print date: 22.01.2021 Revision date: 17.01.2021 EN
Version: 3.0004 Issue date: 17.01.2021 Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier) XG20000AAJ10
Trade name/designation AquaSeal ExoBloc

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

paint and/or paint related material
Reserved for industrial and professional use.

Uses advised against

Do not use for injecting or spraying.

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

Berger-Seidle GmbH
Parkettlacke - Klebstoffe - Bauchemie Telephone: +49 6359 / 8005-0
Maybachstraße 2 Telefax: +49 6359 / 8005-170
67269 Grünstadt
Germany

Department responsible for information:

Laboratory
E-mail Sicherheitsdaten@berger-seidle.de

1.4. Emergency telephone number

24-hour emergency number: +49 700 24112112
(BLG)
24-hour emergency number in side USA: +11 49 700 24112112 (BLG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Hazard statements

not applicable

Precautionary statements

not applicable

Hazard components for labelling

not applicable

Supplemental hazard information

EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

Other information

Read label before use. If medical advice is needed, have product container or label at hand. Keep out of reach of children.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Description Water-based surface finishes, solvent content up to 15%, N-methylpyrrolidone-free

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. **REACH No.**

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: XG20000AAJ10 AquaSeal ExoBloc
Print date: 22.01.2021 Revision date: 17.01.2021
Version: 3.0004 Issue date: 17.01.2021

EN
Page 2 / 8

| CAS No. Index No. | Designation classification // Remark | weight-% |
|-------------------------|---|----------|
| 252-104-2 34590-94-8 | 01-2119450011-60-XXXX (2-methoxymethylethoxy)propanol Substance with a common (EC) occupational exposure limit value. | 7,5 - 10 |

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

Article No.: XG20000AAJ10 AquaSeal ExoBloc
Print date: 22.01.2021 Revision date: 17.01.2021
Version: 3.0004 Issue date: 17.01.2021

EN
Page 3 / 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

WEL, TWA: 308 mg/m³; 50 ppm

Remark: (may be absorbed through the skin)

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

DNEL long-term dermal (systemic), Workers: 283 mg/kg

DNEL long-term inhalative (systemic), Workers: 308 mg/m³

DNEL long-term dermal (systemic), Consumer: 121 mg/kg

DNEL long-term inhalative (systemic), Consumer: 37,2 mg/m³

DNEL long-term exposure oral (systemic effects), Consumer: 36 mg/kg

PNEC:

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

PNEC aquatic, freshwater: 19 mg/L

PNEC aquatic, marine water: 1,9 mg/L

PNEC aquatic, intermittent release: 190 mg/L

PNEC sediment, freshwater: 70,2 mg/kg

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: XG20000AAJ10 AquaSeal ExoBloc
Print date: 22.01.2021 Revision date: 17.01.2021
Version: 3.0004 Issue date: 17.01.2021

EN
Page 4 / 8

PNEC sediment, marine water: 7,02 mg/kg
PNEC, soil: 2,74 mg/kg
PNEC sewage treatment plant (STP): 4168 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state:

Liquid

Colour:

white

Odour:

characteristic

Odour threshold:

not applicable

pH at 20 °C:

4 - 4,9 / 100,0 weight-%

Melting point/freezing point:

not applicable

Initial boiling point and boiling range:

100 °C

Flash point:

not applicable

Evaporation rate:

not applicable

flammability

Burning time:

not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit:

not applicable

Upper explosion limit:

not applicable

Vapour pressure at 20 °C:

23 mbar

Method: calculated.

Vapour density:

not applicable

Relative density:

Density at 20 °C:

1,02 g/cm³

Solubility(ies):

Water solubility at 20 °C:

partially soluble

Partition coefficient: n-octanol/water:

see section 12

Auto-ignition temperature:

not applicable

Article No.: XG20000AAJ10 AquaSeal ExoBloc
Print date: 22.01.2021 Revision date: 17.01.2021
Version: 3.0004 Issue date: 17.01.2021

EN
Page 5 / 8

Decomposition temperature: not applicable
Viscosity at 20 °C: 20 s 4 mm
Method: DIN 53211
Explosive properties: not applicable
Oxidising properties: not applicable
9.2. **Other information**
Solvent separation test: < 3 weight-% (ADR/RID)

SECTION 10: Stability and reactivity

- 10.1. **Reactivity**
No information available.
- 10.2. **Chemical stability**
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.3. **Possibility of hazardous reactions**
Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
- 10.4. **Conditions to avoid**
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.
- 10.5. **Incompatible materials**
not applicable
- 10.6. **Hazardous decomposition products**
Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

(2-methoxymethylethoxy)propanol
oral, LD50, Rat: > 5000 mg/kg
dermal, LD50, Rabbit: > 5000 mg/kg

Skin corrosion/irritation; Serious eye damage/eye irritation

(2-methoxymethylethoxy)propanol
Skin
no irritation
eyes: Evaluation no irritation

Respiratory or skin sensitisation

(2-methoxymethylethoxy)propanol
: ; Evaluation No sensitising effect known

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

(2-methoxymethylethoxy)propanol
Evaluation No data available

Aspiration hazard

(2-methoxymethylethoxy)propanol
Aspiration hazard; Evaluation Represents no obvious danger of aspiration due to its physical properties

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are:

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: XG20000AAJ10 AquaSeal ExoBloc
Print date: 22.01.2021 Revision date: 17.01.2021
Version: 3.0004 Issue date: 17.01.2021

EN
Page 6 / 8

headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

(2-methoxymethylethoxy)propanol

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 10000 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1919 mg/L (48 h)

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

(2-methoxymethylethoxy)propanol

: 75 % (28 D); Evaluation Readily biodegradable (according to OECD criteria).

Method: OECD F

: 93 % (13 D)

Method: OECD 302B/ ISO 9888/ EEC 92/69/V, C.9

12.3. Bioaccumulative potential

(2-methoxymethylethoxy)propanol

Partition coefficient: n-octanol/water: 1,01

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

(2-methoxymethylethoxy)propanol

: Evaluation No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

14.2. UN proper shipping name

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: XG20000AAJ10 AquaSeal ExoBloc
Print date: 22.01.2021 Revision date: 17.01.2021 EN
Version: 3.0004 Issue date: 17.01.2021 Page 7 / 8

14.3. **Transport hazard class(es)**
not applicable

14.4. **Packing group**
not applicable

14.5. **Environmental hazards**
Land transport (ADR/RID) not applicable
Marine pollutant not applicable

14.6. **Special precautions for user**
Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code -

Sea transport (IMDG)

EmS-No. not applicable

14.7. **Transport in bulk according to Annex II of Marpol and the IBC Code**
not applicable

SECTION 15: Regulatory information

15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L) ISO 11890-2: 99
VOC-value (in g/L) ASTM D2369: 236

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/i) ; VOC limit value: 140 g/l
Maximum VOC content (g/L) of the product in a ready to use condition: 99

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
MAL-Kode (MAL Kode ready-to-use): 0-1

15.2. **Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

| | |
|----------|---|
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| OEL | Occupational Exposure Limit Value |
| BLV | Biological Limit Value |
| CAS | Chemical Abstracts Service |
| CLP | Classification, Labelling and Packaging |
| CMR | Carcinogenic, Mutagenic and Reprotoxic |
| DIN | German Institute for Standardization / German industrial standard |
| DNEL | Derived No-Effect Level |
| EAKV | European Waste Catalogue Directive |
| EC | Effective Concentration |
| EC | European Community |
| EN | European Standard |
| IATA-DGR | International Air Transport Association – Dangerous Goods Regulations |
| IBC Code | International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk |

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: XG20000AAJ10 AquaSeal ExoBloc
Print date: 22.01.2021 Revision date: 17.01.2021
Version: 3.0004 Issue date: 17.01.2021

EN
Page 8 / 8

| | |
|-----------|---|
| ICAO-TI | International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air |
| IMDG Code | International Maritime Code for Dangerous Goods |
| ISO | International Organization for Standardization |
| LC | Lethal Concentration |
| LD | Lethal Dose |
| MARPOL | Maritime Pollution: The International Convention for the Prevention of Pollution from Ships |
| OECD | Organisation for Economic Cooperation and Development |
| PBT | persistent, bioaccumulative, toxic |
| PNEC | Predicted No Effect Concentration |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| UN | United Nations |
| VOC | Volatile Organic Compounds |
| vPvB | very persistent and very bioaccumulative |

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.