



**Made in Germany!**  
Importer: Ltd "Abschliff Latvija"  
Riga, A Čaka iela 107 K2  
Phone: +371 67843844, 67843845  
Fakss: +371 67272792  
Mob.: +371 26177888  
E-mail: [info@abschliff.lv](mailto:info@abschliff.lv)  
[www.abschliff.lv](http://www.abschliff.lv)

<https://www.facebook.com/Abschliff-Latvija-100679528475676/>



Open: Monday to Friday – 9<sup>00</sup>-18<sup>00</sup>, Saturday- 10<sup>00</sup>-14<sup>00</sup>, Sunday – closed

## Avalon Teak Oil - oil for wood (for exterior woodwork)

### Description

Teak Oil is a high quality product based on vegetable oils and resins for all types of exterior wood such as fences, pergola, play ground timber, wooden terraces and decks, teak furniture and garden furniture. Suitable especially for tropical woods such as bangkirai and teak. Saliva- and perspiration resistant according to DIN 53160.

### Colour

Transparent, colourless to slightly yellow. Light and absorbent surfaces will dry slightly darker. Woodwork will react differently in colour according to the nature of the wood and the structure of the wood grain.

### Ingredients

Linseed oil, castor oil, wood oil, isoparaffins, iodo-propynyl-butylcarbamate, drying agents. Product contains max 420 g/l VOC. EU limit value for this product (cat. f): 700 g/l (2010).

### Hazard statements

May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects. GHS08



### Application

Stir well before use. Apply by brush thinly and evenly. Avoid ponding. Ambient- and surface temperature must be higher than +10°C.

### Drying time

Approx. 16 - 24 hours. It is essential to provide adequate ventilation during the drying process!

### Packaging and consumption

Approx. 50 - 70 ml/m<sup>2</sup> per coat depending on the absorbency of the surface.

Packaging: 0.25l for 4 m<sup>2</sup>, 0.75l for 12,5 m<sup>2</sup>, 2.5l for 41,5 m<sup>2</sup>

### Storage

Originally sealed at least 5 years stable. Store dry, cool and sealed.

### Disposal

According to locally regulated laws. European Waste Catalogue (EWC) 08 01 11.

### Cleaning up

Clean surfaces with neutral detergents in lukewarm water. Clean equipments immediately after use with solvents.

### Precautionary statements

Repeated exposure may cause skin dryness or cracking. Contains Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction. Active ingredient: Iodo-2-propynyl-butylcarbamate <0,6%

Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment.

Dispose of contents/container according to local regulations. Always be sure to store cleaning cloth, polishing pads, sponges, etc. that are still wet or even slightly moist with product in an airtight metal container or in water and dispose, as there is a danger of spontaneous combustion caused by the plant oil content in the product. The product alone will not undergo spontaneous combustion.

A typical smell may arise due to the natural raw materials. During sanding wear mask against respirable dust.

