according to Regulation (EC) No 1907/2006

AVALON Hartwachsöl, farbig

Revision date: 26.09.2024 Product code: Av-290-xxx-01 Page 1 of 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

AVALON Hartwachsöl, farbig

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Vegetable resin paints Paints and varnishes

## Uses advised against

No information available.

No further relevant information available.

## 1.3. Details of the supplier of the safety data sheet

Company name: SIA Abschliff Latvija Street: A.Èaka iela 107

Place: LV-1011 Riga LV-1011 Telephone: + 371 67843844, +371

26177888

E-mail: info@abschliff.lv
E-mail (Contact person): info@abschliff.lv
Internet: www.abschliff.lv
Responsible Department: + 371- 67843844

+ 371 26177888 (mobile)

1.4. Emergency telephone

number:

112

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

### Regulation (EC) No 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

## Regulation (EC) No 1272/2008

## **Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

### **Precautionary statements**

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

P273 Avoid release to the environment.

### Special labelling of certain mixtures

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe

spray or mist.

## 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Spontaneous ignition possible through autoxidation of cloths soaked in the product.

### **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

## Relevant ingredients

## according to Regulation (EC) No 1907/2006

	AVALON Hartwachsöl, farbig	
Revision date: 26.09.2024	Product code: Av-290-xxx-01	Page 2 of 9

CAS No	Chemical name		Quantity	
	EC No	Index No	REACH No	
	Classification (Regulation (EC)	No 1272/2008)		
64742-96-7	isoalkane			40 - 50 %
	265-200-4			
	Asp. Tox. 1; H304 EUH066			
13463-67-7	titanium dioxide			1-< 8 %
	236-675-5	022-006-00-2		
	Carc. 2; H351			
1314-13-2	zinc oxide		0,1-< 0,9 %	
	215-222-5	030-013-00-7		
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
27253-32-3	Manganese Neodecanoate		0,1-0,5 %	
	248-374-6			
	STOT RE 2; H373			
39049-04-2	Zirconium neodecanacis salt			0,1- < 0,5 %
	254-259-1		01-2120770770-52	
64216-15-5	Calcium 3,5,5-trimethylhexanoat		0,1- < 0,5 %	
	264-731-9		01-2119978299-15	
	Acute Tox. 4, Eye Irrit. 2; H302	H319		

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

opositio conta attituto, in factore and / til			
CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1314-13-2	215-222-5	zinc oxide	0,1-< 0,9 %
	oral: LD50 =	: > 5000 mg/kg	
64216-15-5	264-731-9	Calcium 3,5,5-trimethylhexanoat	0,1- < 0,5 %
	oral: ATE =	500 mg/kg	

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### **General information**

When in doubt or if symptoms are observed, get medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

## After inhalation

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

### After contact with skin

Immediately remove any contaminated clothing, shoes or stockings.

After contact with skin, wash immediately with plenty of water and soap.

Do not wash with: Solvents/Thinner

## After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

## After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

according to Regulation (EC) No 1907/2006

AVALON Hartwachsöl, farbig

Revision date: 26.09.2024 Product code: Av-290-xxx-01 Page 3 of 9

Do NOT induce vomiting.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Extinguishing powder, Water mist

### Unsuitable extinguishing media

Full water jet

## 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Hazardous decomposition products: carbon black. Danger of serious damage to health by prolonged exposure. Use appropriate respiratory protection.

## 5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### **General advice**

Keep away from sources of ignition - No smoking. Ventilate affected area.

Avoid breathing dust/fume/gas/mist/vapours/spray.

See protective measures under point 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

### Other information

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal. Disposal: see section 13

Clean with detergents. Avoid solvent cleaners.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

### Advice on safe handling

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away.

Use explosion-proof electrical equipment. Filling and transfer: Take precautionary measures against static discharges. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink or smoke.

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

### Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

### Further information on handling

## 7.2. Conditions for safe storage, including any incompatibilities

according to Regulation (EC) No 1907/2006

AVALON Hartwachsöl, farbig

Revision date: 26.09.2024 Product code: Av-290-xxx-01 Page 4 of 9

### Requirements for storage rooms and vessels

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV).

#### Hints on joint storage

Do not store together with: Oxidising agent, Strong acid, Strong alkali

## Further information on storage conditions

Follow the instructions for use on the label. storage temperature of °C 5 up to °C 30.

Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

### 7.3. Specific end use(s)

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### 8.2. Exposure controls

## Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

### Individual protection measures, such as personal protective equipment

### Eye/face protection

Wear eye/face protection.

### Hand protection

Wear suitable gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. See information supplied by the manufacturer.

Suitable material: Nitrilkautschuk Breakthrough time:: >= 8 hmin.

Use protective skin cream before handling the product.

## Skin protection

Wear anti-static footwear and clothing (Natural fibres (e.g. cotton) / heat-resistant synthetic fibres)

#### Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values.

Use suitable breathing apparatus.

## **Environmental exposure controls**

Do not allow to enter into surface water or drains.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: liquid: Colour: various Odour: mild

**Test method** 

Melting point/freezing point: not applicable ASTM D 1120

Boiling point or initial boiling point and > 180 °C

boiling range:

Lower explosion limits: 0,6 g/m³
Upper explosion limits: 7,0 g/m³

Flash point: > 61 °C DIN 53213

according to Regulation (EC) No 1907/2006

	AVALON Hartwachsöl, farbig	
Revision date: 26.09.2024	Product code: Av-290-xxx-01	Page 5 of 9

Auto-ignition temperature: ASTM D 1929

pH-Value: not relevant ASTM D 1287:2011

Viscosity / kinematic (at 40 °C): > 20,5 mm<sup>2</sup>/s

Water solubility: This information is not available. Partition coefficient n-octanol/water: This information is not available.

Density (at 20 °C): 0,95-1,06 g/cm<sup>3</sup> ASTM D 792

Bulk density: NF T 20-053

Relative vapour density: This information is not available.

Particle characteristics: not relevant

### 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties

not relevant

Sustaining combustion: UN Test L.2

Self-ignition temperature

Solid: n.a.

Oxidizing properties not relevant

## Other safety characteristics

Solvent separation test: not relevant
Sublimation point: not relevant n.a.
Softening point: n.a.
Pour point: n.a.

Flow time (at 40 °C): > 60 s 3 DIN EN ISO 2431

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidising agent, Strong acid, Strong alkali

### 10.4. Conditions to avoid

In case of warming: Formation of: Hazardous decomposition products

### 10.5. Incompatible materials

Oxidizing agent

### 10.6. Hazardous decomposition products

Nitrogen oxides (NOx), carbon black, Carbon dioxide (CO2), Carbon monoxide

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

## according to Regulation (EC) No 1907/2006

	AVALON Hartwachsöl, farbig	
Revision date: 26.09.2024	Product code: Av-290-xxx-01	Page 6 of 9

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1314-13-2	zinc oxide				
	oral	LD50 > 5000 mg/kg	Rat	IUCLID	
64216-15-5	Calcium 3,5,5-trimethylhexanoat				
	oral	ATE 500 mg/kg			

## Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

## Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

Observe risk of aspiration if vomiting occurs.

### **Practical experience**

Following inhalation:

Potential hazards: May cause respiratory irritation. Depression of central nervous system.

Symptoms: Headache, Dizziness, Dizziness, Unconsciousness

After eye contact:

Irritating to eyes. (reversible.)

Following ingestion:

Symptoms: Nausea, Vomiting, Gastrointestinal complaints

## Following skin contact:

The product is skin resorptive. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

## 11.2. Information on other hazards

### Other information

### **Further information**

There are no data available on the mixture itself.

Reference to other sections: 2, 3

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

### 12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

### 12.4. Mobility in soil

according to Regulation (EC) No 1907/2006

AVALON Hartwachsöl, farbig

Revision date: 26.09.2024 Product code: Av-290-xxx-01 Page 7 of 9

Based on available data, the classification criteria are not met.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No data available

#### **Further information**

There are no data available on the mixture itself.

Do not allow to enter into surface water or drains.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains.

Dispose according to legislation.

### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

## List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

### Contaminated packaging

Completely emptied packages can be recycled.

Dispose according to legislation.

#### **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

#### Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4 Packing group:	No dangerous good in sense of this transport regulation

### Marine transport (IMDG)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

according to Regulation (EC) No 1907/2006

AVALON Hartwachsöl, farbig

Revision date: 26.09.2024 Product code: Av-290-xxx-01 Page 8 of 9

14.2. UN proper shipping name:
 14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

**ENVIRONMENTALLY HAZARDOUS: No** 

### 14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 75

Directive 2004/42/EC on VOC in

425 g/l/l:

paints and varnishes:

Subcategory according to Directive 2004/42/EC:

Interior and exterior minimal build woodstains - Solvent-borne coatings, VOC

limit value: 700 g/l

Information according to Directive

2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

**National regulatory information** 

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under

the Maternity Protection Directive (92/85/EEC) for expectant or nursing

mothers.

Water hazard class (D): 1 - slightly hazardous to water

**Additional information** 

Observe in addition any national regulations!

## **SECTION 16: Other information**

### Abbreviations and acronyms

Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Eye Irrit: Eye irritation Carc: Carcinogenicity

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

## Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

according to Regulation (EC) No 1907/2006

AVALON Hartwachsöl, farbig

Revision date: 26.09.2024 Product code: Av-290-xxx-01 Page 9 of 9

## Relevant H and EUH statements (number and full text)

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray

or mist.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)